

CA 2413

Planar Antenna

Order # 464.252



FEATURES

- Polarization, circular left or right
- With SMA socket
- Suitable for remote mounting on a wall
- Supplied with wall mounting

APPLICATIONS

The CA 2413 planar antenna is fitted with a SMA socket and suitable for remote mounting. The antenna is supplied with a wall mounting.

TECHNICAL SPECIFICATIONS

Frequency range	2300 - 2500 MHz
Impedance	50 Ω
VSWR	1.5
Polarization	circular, left or right
Gain	8.5 dBi
Beamwidth horizontal, 3 dB	70°
Beamwidth vertical, 3 dB	65°
Downtilt	0°
Front to back ratio	20 dB
Axial ratio	3.0 dB
Max. power	75 W (CW) at 25°C
Dimensions	101 x 95 x 32 mm
Weight	0.1 kg
Housing material	ASA and aluminium
Material of wall mounting	ASA
Housing colour	RAL 7035 (light grey)
Colour of wall mounting	RAL 7042 (dark grey)
Operating temperature range	-40°C to +80°C
Storage temperature range	-40°C to +80°C
Windload	15 N at 160 km/h

Germany

Theresienstr. 8
D-74072 Heilbronn
Tel. +49 (0)71 31 / 6 17-0
Fax +49 (0)71 31 / 617-224
E-mail: info@beyerdynamic.de
Internet: www.beyerdynamic.de



United States

56 Central Ave.
Farmingdale, NY 11735
Tel. +1 (631) 293-3200
Fax +1 (631) 293-3288
E-mail: salesUSA@beyerdynamic-usa.com
Internet: www.beyerdynamic-usa.com

Great Britain

17 Albert Drive
Burgess Hill RH15 9TN
Tel. +44 (0)1444 / 258 258
Fax +44 (0)1444 / 258 444
E-mail: sales@beyerdynamic.co.uk
Internet: www.beyerdynamic.co.uk

POLAR PATTERN



DIMENSIONS

